

TFT DISPLAY SPECIFICATION



WINSTAR Display Co.,Ltd.
華凌光電股份有限公司



SPECIFICATION

MODULE NO.: WF80GSYAUMNNO#

General Specifications

Item	Dimension	Unit
Size	8.0	inch
Dot Matrix	800× 3(RGB) ×1280	dots
Module dimension	115.74 × 184.93 × 4.75	mm
Active area	107.64 × 172.224	mm
Pixel pitch	0.13455 x 0.13455	mm
LCD type	TFT, Normally Black, Transmissive	
Viewing angle	85/85/85/85	
TFT Drive IC	ILI9881C or Equivalent	
TFT Interface	4-Lanes MIPI	
Aspect Ratio	10:16	
Backlight Type	LED, Normally White	
Touch Panel	Without Touch Panel	
Surface	Glare	

*Color tone slight changed by temperature and driving voltage.

Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	°C
Storage Temperature	TST	-30	—	+80	°C

Electrical Characteristics

Typical Operation Conditions

Item	Symbol	Values			Unit
		Min.	Typ.	Max.	
Power supply for analog circuit	VCI	3.0	3.3	3.6	V
Power supply for logic circuit	IOVCC	1.65	1.8	3.6	V
Current for Driver	I _{vci}	-	45	70	mA
	I _{ioVCC}	-	20	30	mA

Interface

1.LCM PIN Definition

1-9	NC	No connection
10-11	VCI	Power supply for analog circuits. Connect to an external power supply of 3.0V to 3.6V
12-13	NC	No connection
14	RESET	The external reset input (RESX) Initializes the chip with a low input. Be sure to execute a power-on reset after supplying power. Fix to IOVCC level when not in use.
15	TE	Tearing effect output pin. Leave the pin open when not in use.
16	NC	No connection (LED PWM)
17-18	GND	Power ground
19-20	IOVCC	Power supply for analog circuits. Connect to an external power supply of 1.65V to 3.6V
21	GND	Power ground
22	D3P	MIPI DSI differential data pair. (Data lane 3)
23	D3N	
24	GND	Power ground
25	D2P	MIPI DSI differential data pair. (Data lane 2)
26	D2N	
27	GND	Power ground
28	CLKP	MIPI DSI differential clock pair
29	CLKN	
30	GND	Power ground
31	D1P	MIPI DSI differential data pair. (Data lane 1)
32	D1N	
33	GND	Power ground
34	D0P	MIPI DSI differential data pair. (Data lane 0)
35	D0N	
36	GND	Power ground
37	VLED1+	Power for LED1 backlight anode
38	VLED2+	Power for LED2 backlight anode
39	VLED1-	Power for LED1 backlight cathode
40	VLED2-	Power for LED2 backlight cathode

WINSTAR DISPLAY CO., LTD

Contour Drawing

