

# TFT DISPLAY SPECIFICATION



**WINSTAR Display Co.,Ltd.**  
**華凌光電股份有限公司**



# Winstar Display Co., LTD

## 華凌光電股份有限公司



WEB: <https://www.winstar.com.tw> E-mail: sales@winstar.com.tw

### SPECIFICATION

**MODULE NO.: WF35UTYAIMNG0#**

### General Specification

Item	Dimension	Unit
Size	3.5	inch
Dot Matrix	320 x RGB x 480(TFT)	dots
Module dimension	68.7 (W) x 95.6 (H) x 4.61(D)	mm
Active area	48.96 x 73.44	mm
Pixel pitch	0.153 × 0.153	mm
LCD type	TFT, Normally Black, Transmissive	
View Direction	80/80/80/80	
Aspect Ratio	Portrait	
TFT Driver IC	ILI9488 or Equivalent	
TFT Interface	1-Lane MIPI	
Backlight Type	LED, Normally White	
CTP IC	GT911 or Equivalent	
CTP Interface	I2C	
CTP FW Version	95	
CTP Resolution	320*480	
Touch Panel	With PCAP	
Surface	Glare	

\*Color tone slight changed by temperature and driving voltage.

# Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	°C
Storage Temperature	TST	-30	—	+80	°C

# Electrical Characteristics

## 1. Operating conditions:

Item	Symbol	Condition	Min	Typ	Max	Unit
Supply Voltage for digital	IOVCC	—	1.8	3.0	3.3	V
Supply Voltage for analog	VCI	—	2.8	3.0	3.3	V
Power Supply for Current	ICC	IOVCC=VCI =VCC=3.3V	—	13.5	20.5	mA
Supply Voltage For Touch Logic	VDDT	—	2.8	—	3.3	V
	IDDT	VDDT=3.3V	—	10	15	mA

## 2. LED driving conditions

Parameter	Symbol	Min	Typ	Max	Unit
LED current	—	—	160	—	mA
LED voltage	LEDA	2.7	3.2	3.4	V
LED Life Time	—	—	50000	—	Hr

# Interface

## 1. LCM PIN Definition

NO	Symbol	Function	I/O
1	VCI	A supply voltage to the analog circuit. Connect to an external power supply of 2.5 ~ 3.3V. Connect to a stabilizing capacitor between VCI and GND.	P
2	IOVCC	A supply voltage to the digital circuit. Connect to an external power supply of 1.65 ~ 3.3V.	P
3	RESET	Reset input signal Initialize the chip with a low input. Be sure to execute a power-on reset after supplying power.	I
4	GND	Ground	I
5	MIPI_CLK_P	Positive polarity of low voltage differential clock signal Leave the pin open when not in use.	I
6	MIPI_CLK_N	Negative polarity of low voltage differential clock signal Leave the pin open when not in use	I
7	GND	Ground	I
8	MIPI_DATA_P	Positive polarity of low voltage differential data signal Leave the pin open when not in use.	I
9	MIPI_DATA_N	Negative polarity of low voltage differential data signal Leave the pin open when not in use.	I
10	GND	Ground	I
11	VLED+	Anode of LED backlight.	
12	VLED-	Cathode of LED backlight	

## 2. CTP PIN Definition

Pin	Symbol	Function
1	VSS	Connect to system ground.
2	VDDT	Power Supply
3	SCL	I2C clock input
4	NC	No connect
5	SDA	I2C data input and output
6	NC	No connect
7	RST	External Reset, Low is active
8	NC	No connect
9	INT	External interrupt to the host
10	VSS	Connect to system ground.

# Contour Drawing

