

TFT DISPLAY SPECIFICATION



WINSTAR Display Co.,Ltd.
華凌光電股份有限公司



Winstar Display Co., LTD

華凌光電股份有限公司



WEB: <https://www.winstar.com.tw> E-mail: sales@winstar.com.tw

SPECIFICATION

MODULE NO.: WF35LTIACDNT0#

General Specifications

Item	Dimension	Unit
Size	3.5	inch
Dot Matrix	320 x RGBx240(TFT)	dots
Module dimension	76.84x 63.84x 4.37	mm
Active area	70.08 x 52.56	mm
Dot pitch	0.073 x 0.219	mm
LCD type	TFT, Normally White, Transmissive	
View Direction	12o'clock	
Gray Scale Inversion Direction	6 o'clock	
TFT Driver IC	HX8238 or Equivalent	
TFT Interface	24-bit RGB or option other mode	
Aspect Ratio	4:3	
Backlight Type	LED ,Normally White	
Touch Panel	Resistive Touch Panel (RTP)	
Surface	Anti-Glare	

Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	°C
Storage Temperature	TST	-30	—	+80	°C

Electrical Characteristics

Operating conditions :

Item	Symbol	Min	Typ	Max	Unit
Supply Voltage For LCM	VCC	3.0	3.3	3.6	V
Supply Current For LCM	ICC	—	8.6	15	mA

LED driving conditions :

Parameter	Symbol	Min.	Typ.	Max.	Unit
LED current		-	20	-	mA
Power Consumption		336	384	408	mW
LED voltage	LED+	16.8	19.2	20.4	V
LED Life Time		-	50,000	-	Hr

Interface

LCM PIN Definition

Pin	Symbol	Function
1	LED-	Power for LED backlight cathode
2	LED-	Power for LED backlight cathode
3	LED+	Power for LED backlight anode
4	LED+	Power for LED backlight anode
5	YU	Top electrode
6	XL	Left electrode
7	NC	No connect
8	/RESET	Hardware reset
9	SPENA	Chip select pin of serial interface
10	SPCLK	Clock pin of serial interface (SPCK)
11	SPDAT	Data input pin in serial mode(SPDA)
12	B0	Data bus
13	B1	Data bus
14	B2	Data bus
15	B3	Data bus
16	B4	Data bus
17	B5	Data bus
18	B6	Data bus
19	B7	Data bus
20	G0	Data bus
21	G1	Data bus
22	G2	Data bus
23	G3	Data bus
24	G4	Data bus
25	G5	Data bus
26	G6	Data bus
27	G7	Data bus
28	R0	Data bus
29	R1	Data bus
30	R2	Data bus

31	R3	Data bus
32	R4	Data bus
33	R5	Data bus
34	R6	Data bus
35	R7	Data bus
36	HSYNC	Line synchronization signal
37	VSYNC	Frame synchronization signal
38	DCLK	Dot-clock signal and oscillator source
39	NC	No connect
40	NC	No connect
41	VCC	Power Supply
42	VCC	Power Supply
43	YD	Bottom electrode
44	XR	Right electrode
45	NC	No connect
46	NC	No connect
47	NC	No connect
48	SEL2	Input pin to select input interface mode
49	SEL1	Input pin to select input interface mode
50	SEL0	Input pin to select input interface mode
51	NC	No connect
52	DE	Display enable pin from controller. Internal pull high Connect to VCCIO or floating if not used
53	DGND	System ground pin of the IC. Connect to system ground.
54	AVSS	Grounding for analog circuit Connect to system ground

Contour Drawing

