

TFT DISPLAY SPECIFICATION



WINSTAR Display Co.,Ltd.
華凌光電股份有限公司



SPECIFICATION

MODULE NO.: WF70D3TIAGDNN0#

General Specifications

Item	Dimension	Unit
Size	7.0	inch
Dot Matrix	800 x RGB x 480 (TFT)	dots
Module dimension	165 x 100.0 x 5.7	mm
Active area	154.08 x 85.92	mm
Pixel Pitch	0.1926 x 0.179	mm
LCD type	TFT, Normally White, Transmissive	
View Direction	12 o'clock	
Gray Scale Inversion Direction	6 o'clock	
Aspect Ratio	16:9	
Backlight Type	LED ,Normally White	
Color arrangement	RGB- Stripe	
TFT Driver IC	ILI6137A +ILI5960-9G or equivalent	
TFT Interface	24-bit RGB	
Touch Panel	Without Touch Panel	
Surface	Anti-Glare	

*Color tone slight changed by temperature and driving voltage.

Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	°C
Storage Temperature	TST	-30	—	+80	°C

Electrical Characteristics

1. Operating conditions:

Item	Symbol	Min	Typ	Max	Unit
Supply Voltage For Logic	VCC	3.0	3.3	3.6	V
Power voltage	AVDD	10.2	10.4	10.6	V
Power Supply For Current	VCC =3.3V	-	3.1	-	mA
Power voltage	VGH	14.5	15.0	15.5	V
Power voltage	VGL	-10.5	-10	-9.5	V
Input signal voltage	VCOM	3.54	4.04	4.54	V
Power AVDD For Current	IADD	-	13.7	-	mA
Power VGH For Current	IGH	-	0.57	-	mA
Power VGL For Current	IGL	-	0.63	-	mA
Power VCOM For Current	ICOM	-	0.03	-	mA

2. LED driving conditions

Parameter	Symbol	Min.	Typ.	Max.	Unit
LED current	I _{LED}	-	180	-	mA
Power Consumption	-	1512	1764	1980	mW
LED voltage	V _{LED+}	8.4	9.8	11.0	V
LED Life Time	-	50,000		-	Hr

Interface

1. LCM PIN Definition

Pin	Symbol	Function
1	VLED+	Power supply for backlight
2	VLED+	Power supply for backlight
3	VLED-	Backlight ground
4	VLED-	Backlight ground
5	GND	Power ground
6	VCOM	Common voltage
7	VCC	Power for Digital Circuit
8	MODE	DE/SYNC mode select
9	DE	Data Input Enable (DEN)
10	VS	Vertical Sync Input (VSD)
11	HS	Horizontal Sync Input (HSD)
12	B7	Blue data(MSB)
13	B6	Blue data
14	B5	Blue data
15	B4	Blue data
16	B3	Blue data
17	B2	Blue data
18	B1	Blue data
19	B0	Blue data(LSB)
20	G7	Green data(MSB)
21	G6	Green data
22	G5	Green data
23	G4	Green data
24	G3	Green data
25	G2	Green data
26	G1	Green data
27	G0	Green data(LSB)
28	R7	Red data(MSB)
29	R6	Red data
30	R5	Red data
31	R4	Red data

32	R3	Red data
33	R2	Red data
34	R1	Red data
35	R0	Red data(LSB)
36	GND	Power Ground
37	DCLK	Sample clock (CLK)
38	GND	Power Ground
39	L/R	Left / right selection
40	U/D	Up/down selection
41	VGH	Gate ON Voltage
42	VGL	Gate OFF Voltage
43	AVDD	Power for Analog Circuit
44	RESET	Global reset pin.
45	NC	No connection
46	VCOM	Common Voltage
47	DITHB	Dithering function
48	GND	Power Ground
49	NC	No connection
50	NC	No connection

I: input, O: output, P: Power

Technical drawing of the TFT FPC assembly, showing dimensions and a pin list.

Top View Dimensions:

- Overall width: 165.00
- Overall height: 100.00
- VA (Vertical Alignment) area: 157.00
- AA (Active Area) width: 154.08
- RGB area: 800 X RGB X 480
- Beating Area: 7.85±0.5
- Stiffener width: 25.50
- Overall length: 68.17±0.5
- Overall height (including stiffener): 45.59±0.5
- VA area height: 89.50
- AA area height: 85.92
- VA area width: 165.00
- AA area width: 154.08
- VA area height (including stiffener): 100.00
- AA area height (including stiffener): 85.92
- VA area width (including stiffener): 165.00
- AA area width (including stiffener): 154.08

Side View Dimensions:

- Overall height: 5.70±0.3
- Stiffener height: 2.00Max
- Stiffener width: 0.30±0.05
- Contact side

Detail View Dimensions:

- Overall width: 40.00
- Overall height: 32.59±0.5
- VA area height: 25.09±0.5
- AA area height: 18.59±0.5
- VA area width: 8.09±0.5
- AA area width: 10.30±0.5
- VA area height (including stiffener): 32.59±0.5
- AA area height (including stiffener): 18.59±0.5
- VA area width (including stiffener): 8.09±0.5
- AA area width (including stiffener): 10.30±0.5

Pin List:

PIN NO.	SYMBOL
1	VLED+
2	VLED+
3	VLED-
4	VLED-
5	GND
6	VCOM
7	VCC
8	MODE
9	DE
10	VS
11	HS
12	B7
13	B6
14	B5
15	B4
16	B3
17	B2
18	B1
19	B0
20	G7
21	G6
22	G5
23	G4
24	G3
25	G2
26	G1
27	G0
28	R7
29	R6
30	R5
31	R4
32	R3
33	R2
34	R1
35	R0
36	GND
37	DCLK
38	GND
39	L/R
40	U/D
41	VGH
42	VGL
43	AVDD
44	RESET
45	NC
46	VCOM
47	DITHB
48	GND
49	NC
50	NC

Notes:

- A: SCALE: 5X
- The non-specified tolerance of dimension is ±0.3 mm .

TFT	FPC
PIN NO.	SYMBOL
1	VLED+
2	VLED+
3	VLED-
4	VLED-
5	GND
6	VCOM
7	VCOM
8	MODE
9	DE
10	VS
11	HS
12	B7
13	B6
14	B5
15	B4
16	B3
17	B2
18	B1
19	B0
20	G7
21	G6
22	G5
23	G4
24	G3
25	G2
26	G1
27	G0
28	R7
29	R6
30	R5
31	R4
32	R3
33	R2
34	R1
35	R0
36	GND
37	DCLK
38	GND
39	L/R
40	U/D
41	VGH
42	VGL
43	AVDD
44	RESET
45	NC
46	VCOM
47	DITHB
48	GND
49	NC
50	NC