

TFT DISPLAY SPECIFICATION



WINSTAR Display Co.,Ltd.
華凌光電股份有限公司



Winstar Display Co., LTD

華凌光電股份有限公司



WEB: <https://www.winstar.com.tw> E-mail: sales@winstar.com.tw

SPECIFICATION

MODULE NO.: WF70D4SYAUMNG10#

General Specifications

Item	Dimension	Unit
Size	7.0	inch
Dot Matrix	800× RGB ×1280	dots
Module dimension	131.63 x 188.17 x 8.05	mm
Active area	94.2 x 150.72	mm
Pixel pitch	0.11775 x 0.11775	mm
LCD type	TFT, Normally Black, Transmissive	
Viewing angle	85/85/85/85	
TFT Driver IC	ILI9881C or Equivalent	
TFT Interface	2-Lanes MIPI	
Aspect Ratio	16:9	
Backlight Type	LED ,Normally White	
CTP Driver IC	ILI2511 or equivalent	
CTP Interface	I2C	
CTP FW Version	0x06.0x00.0x00.0x00.0x77.0x88.0x00.0x02	
CTP Resolution	16384*16384	
Touch Panel	With Projected Capacitive Touch Screen (PCAP)	
Surface	Glare	

*Color tone slight changed by temperature and driving voltage.

WINSTAR DISPLAY CO., LTD

Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	°C
Storage Temperature	TST	-30	—	+80	°C

Electrical Characteristics

1. Typical Operation Conditions

Item	Symbol	Values			Unit
		Min.	Typ.	Max.	
Supply voltage	VCI	2.5	3.3	3.6	V
	IOVCC	1.7	1.8	1.9	V
Supply LCM current	Ivci	-	130	195	mA
	IIOVCC	-	18	30	mA

2. Backlight Driving Conditions

Parameter	Symbol	Min.	Typ.	Max.	Unit
LED current	ILED	-	140	-	mA
LED voltage	VLED+	16.8	18.0	19.2	V
LED Life Time		-	30,000	-	Hr

Interface


1. LCM PIN Definition

Pin	Symbol	Function
1	TP_GND	Ground
2	TP_SDA	TP serial interface address and data input/output.
3	TP_SCL	TP serial interface clock input.
4	TP_INT	TP indicate coordinate data ready.
5	TP_RST	System reset signal input, active low.
6	NC(YU)	No connection
7	NC(XL)	No connection
8	NC(YD)	No connection
9	NC(XR)	No connection
10-11	VCI	Power for analog circuit.
12-13	NC	No connection
14	RESET	Global reset pin.
15	TE	Tearing effect output pin. Leave the pin open when not in use.
16	NC	No connection
17-18	GND	Ground
19-20	IOVCC	Power supply for I/O system.
21	GND	Ground
22-23	NC	No connection
24	GND	Ground
25-26	NC	No connection
27	GND	Ground
28	CLKP	MIPI DSI differential clock pair leave it open or fix to LVDSVSS level when not in use
29	CLKN	MIPI DSI differential clock pair leave it open or fix to LVDSVSS level when not in use
30	GND	Ground
31	D1P	MIPI DSI differential data pair.
32	D1N	MIPI DSI differential data pair.
33	GND	Ground
34	D0P	MIPI DSI differential data pair.
35	D0N	MIPI DSI differential data pair.

36-37	GND	Ground
38	VLED+	LED input terminal (Anode)
39-40	VLED-	Ground (Cathode)

WINSTAR DISPLAY CO., LTD

Contour Drawing



The non-specified tolerance of dimension is ±0.3 mm .