

TFT DISPLAY SPECIFICATION



WINSTAR Display Co.,Ltd.
華凌光電股份有限公司



Winstar Display Co., LTD

華凌光電股份有限公司



WEB: <https://www.winstar.com.tw> E-mail: sales@winstar.com.tw

SPECIFICATION

MODULE NO.: WF70C9SYAB4MNC1B#

General Specification

Item	Dimension	Unit
Size	7.0	inch
Dot Matrix	280 x RGB x 1424(TFT)	dots
Module dimension	38.2(H) x 186.62(V) x 5.76(D)	mm
Active area	33.60(H) x 170.88(V)	mm
Pixel pitch	0.12(H) x 0.12(V)	mm
LCD type	TFT, Normally Black, Transmissive	
Viewing Angle	80/80/80/80	
Aspect Ratio	1:5	
TFT Driver IC	OTA7290N-C or equivalent	
TFT Interface	4-Lanes MIPI	
CTP Driver IC	GT911 or equivalent	
CTP Interface	I2C	
CTP FW Version	70	
CTP Resolution	X:1424 , Y:280	
Backlight Type	LED, Normally White	
Touch Panel	Projected Capacitive Touch Panel (PCAP)	
Surface	Glare	

*Color tone slight changed by temperature and driving voltage.

Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	°C
Storage Temperature	TST	-30	—	+80	°C

Electrical Characteristics

TFT LCD Module

Item	Symbol	Min.	Typ.	Max.	Unit
Analog Supply voltage	VCC	3.0	3.3	3.6	V
Analog supply current	I _{cc}	-	115	175	mA
Logic input voltage	VIH	0.7*VCC	-	VCC	V
	VIL	GND	-	0.3*VCC	V
Supply CTP	VDDT	2.8	3.3	3.6	V
	IDDT	-	12.2	20	mA

2. Backlight Driving Conditions

Parameter	Symbol	Min.	Typ.	Max.	Unit
LED current	-	-	240	-	mA
LED voltage	VLED+	5.5	6.0	6.8	V
LED Life Time	-	50,000	-	-	Hr

Interface

LCM PIN Definition

Pin No.	Symbol	Description
1	GND	Ground.
2	D3N	MIPI data input pins
3	D3P	
4	GND	Ground.
5	D2N	MIPI data input pins
6	D2P	
7	GND	Ground.
8	CLKN	MIPI clock input pins.
9	CLKP	
10	GND	Ground.
11	D1N	MIPI data input pins
12	D1P	
13	GND	Ground.
14	D0N	MIPI data input pins
15	D0P	
16	GND	Ground.
17	GND	Ground.
18	TE	Tearing effect output pin to synchronize to frame writing. If not used, open this pin
19	RESET	Reset signal pin
20	GND	Ground.
21-23	VCC	Power supply
24	GND	Ground.
25-26	NC	Not connect
27-28	VLED-	LED cathode
29-30	VLED+	LED anode

2. Touch FPC Pin Assignment

Pin No.	Symbol	Description
1	VSS	Ground
2	INT	Interrupt request to the host
3	RST	Wakeup request from the host
4	SDA	I2C data input and output
5	SCL	I2C clock input
6	VDDT	Power supply

[illegible]