



WINSTAR Display Co.,Ltd.
華凌光電股份有限公司



Winstar Display Co., LTD

華凌光電股份有限公司



WEB: <https://www.winstar.com.tw> E-mail: sales@winstar.com.tw

SPECIFICATION

MODULE NO.: WF43ETLAEDNGC#

General Specifications

Item	Dimension	Unit
Size	4.3	inch
Dot Matrix	480 RGB(H) x 272(V)	dots
Module dimension	105.5 x 67.2 x 4.55 (Typ.)	mm
Active area	95.04(H) x 53.86(V)	mm
Dot pitch	0.198(H) x 0.198(V)	mm
LCD type	TFT, Normally White, Transmissive	
View Direction	6 o'clock	
Gray Scale Inversion Direction	12 o'clock	
TFT Interface	24-bit RGB	
TFT Driver IC	ST7282	
Aspect Ratio	16:9	
Backlight Type	Normally White	
PCAP FW Version	3	
PCAP IC	FT5426DQ8	
PCAP Interface	I2C	
Touch Panel	With PCAP	
Surface	Glare	

*Color tone slight changed by temperature and driving voltage.

Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	°C
Storage Temperature	TST	-30	—	+80	°C

Electrical Characteristics

Driving TFT LCD Panel

Ta = 25 °C

Item	Symbol	MIN	TYP	MAX	Unit	
Supply Voltage	VDD	3.0	3.3	3.6	V	
Supply Voltage For CTP	VDDT	2.8	—	3.3	V	
Input Signal Voltage	Low Level	VIL	GND	-	0.3x VDD	V
	High Level	VIH	0.7x VDD	-	VDD	V
Output Signal Voltage	Low Level	VIL	-	-	0.2x VDD	V
	High Level	VIH	0.8x VDD	-	VDD	V
(Panel + LSI) Power Consumption	Black Mode (60Hz)	-	74		nW	
	Standby	-	50	-	uW	

Interface


1. LCM PIN Definition

No.	Symbol	Description
1	VBL-	Backlight LED Cathode
2	VBL+	Backlight LED Anode.
3	GND	System Ground
4	VDD	Power supply for logic operation
5~12	R0~R7	Data bus
13~20	G0~G7	Data bus
21~28	B0~B7	Data bus
29	GND	System Ground
30	DCLK	Pixel clock signal
31	DISP	Display on/off control
32	HSYNC	Horizontal Sync signal
33	VSYNC	Vertical Sync signal
34	DE	Data Enable
35	NC	No connect
36	GND	System Ground
37-40	NC	No connect

2. PCAP PIN Definition

Pin	Symbol	Function
1	VSS	Ground for analog circuit
2	VDDT	Power Supply : +3.0V
3	SCL	I2C clock input
4	NC	No connect
5	SDA	I2C data input and output
6	NC	No connect
7	/RST	External Reset, Low is active
8	NC	No connect
9	/INT	External interrupt to the host
10	VSS	Ground for analog circuit

Contour Drawing



The non-specified tolerance of dimension is ±0.3 mm .