WINSTAR Display

OLED SPECIFICATION

Model No:

WEA002004C

General Specification

Item	Dimension	Unit	
Number of Characters	20 characters x 4 Lines	_	
Module dimension	92.0 x 31.5 x 5.96 Max.	mm	
View area	72.42 x 22.82	mm	
Active area	70.42 x 20.82	mm	
Dot size	0.57 x 0.57	mm	
Dot pitch	0.60 x 0.60	mm	
Character size	2.97 x 4.77	mm	
Character pitch	3.55 x 5.35	mm	
LCD type	OLED , Monochrome		
Duty	1/32		
IC	SSD1311		
Interface	6800, 8080, SPI, I2C		
Size	2.89 inch		



Interface Pin Function

Pin No.	Symbol	Pin Type	Description		
1	VSS	Р	Ground		
2	VDD	Р	Power supply and power supply for interface logic level.		
3	REGVDD	I	This pin is pulled LOW, internal VDD regulator is disabled (Low voltage I/O application).		
4	D/C#	Ι	This pin is Data/Command control pin connecting to the MCU. When the pin is pulled HIGH, the data at D[7:0] will be interpreted as data. When the pin is pulled LOW, the data at D[7:0] will be transferred to a command register. In I2C mode, this pin acts as SA0 for slave address selection. When serial interface is selected, this pin must be connected to VSS.		
5	R/W# (WR#)		This pin is read / write control input pin connecting to the MCU interface. When 6800 interface mode is selected, this pin will be used as Read/Write (R/W#) selection input. Read mode will be carried out when this pin is pulled HIGH and write mode when LOW. When 8080 interface mode is selected, this pin will be the Write (WR#) input. Data write operation is initiated when this pin is pulled LOW and the chip is selected. When serial or I2C interface is selected, this pin must be connected to VSS.		
6	E/RD#		This pin is MCU interface input. When 6800 interface mode is selected, this pin will be used as the Enable (E) signal. Read/write operation is initiated when this pin is pulled HIGH and the chip is selected. When 8080 interface mode is selected, this pin receives the Read (RD#) signal. Read operation is initiated when this pin is pulled LOW and the chip is selected. When serial or I2C interface is selected, this pin must be connected to VSS.		

7	D0		These pins are bi-directional data bus connecting to the			
8	D1		MCU data bus.			
9	D2		Unused pins are recommended to tie LOW.			
10	D3		When serial interface mode is selected, D0 will be the serial			
11	D4	I/O	Clock input: SCLK; D1 will be the serial data input: SID and D2 will be the serial data output: SOD.			
12	D5					
13	D6		and serve as SDAout, SDAin in application and D0 is the			
14	D7		erial clock input, SCL.			
15	CS#	I	This pin is the chip select input connecting to the MCU. The chip is enabled for MCU communication only when CS# is pulled LOW (active LOW). In I2C mode, this pin must be connected to VSS.			
16	RES#	I	This pin is reset signal input. When the pin is pulled LOW, initialization of the chip is executed. Keep this pin pull HIGH during normal operation.			
17	BS0		setting as described in the following table. BS2, BS1 and BS0 are pin select. Bus Interface selection BS[2:0] Interface			
18	BS1	I	000 Serial Interface 001 Invalid 010 I ² C 011 Invalid 100 8-bit 6800 parallel 101 4-bit 6800 parallel			
19	BS2	R	110 8-bit 8080 parallel 111 4-bit 8080 parallel Note (1) 0 is connected to VSS (2) 1 is connected to VDD			
20	VSS (FRGnd)	Р	Ground			
A						

Absolute Maximum Ratings

Item	Symbol	Min	Max	Unit	Notes
Operating Temperature	TOP	-40	+80	°C	-
Storage Temperature	TST	-40	+85	°C	-
Supply Voltage For Logic	VDD-VSS	-0.3	3.6	v	-

Electrical Characteristics

DC Electrical Characteristics

ltem	Symbol	Condition	Min	Тур	Мах	Unit
Supply Voltage For Logic	VDD-VSS		2.8	3.0	3.3	V
Input High Volt.	VIH	-	0.8xVDD	_	VDD	V
Input Low Volt.	VIL	Q-Y	GND	_	0.2xVDD	V
Output High Volt.	VOH	IOH=-0.5mA	0.8xVDD	_	VDD	V
Output Low Volt.	VOL	10L=0.5mA	GND	_	0.2xVDD	V
Display 50% Pixel on	IDD	VDD=3V	-	110	220	mA