TFT DISPLAY SPECIFICATION



WINSTAR Display Co.,Ltd.

華凌光電股份有限公司

SPECIFICATION

MODULE NO.: WFN0880A2S0YAMNN000

General Specifications

Item	Dimension	Unit
Size	8.8	inch
Dot Matrix	480 x RGB. x 1920	dots
Module dimension	231.3 x 64.3 x 6.3	mm
Active area	218.88 x 54.72	mm
Pixel pitch	0.114 x 0.114	mm
LCD type	TFT, Normally black, Transmissive	
Viewing angle	80/80/80/80	
Backlight Type	LED, Normally White	
TFT Driver IC	OTA7290N-C or Equivalent	
TFT Interface	4 Lanes MIPI (2-Lanes Optional)	
Touch Panel	Without Touch Panel	
Surface	Anti-Glare	

*Color tone slight changed by temperature and driving voltage.

WINSTAR DISPLAY CO.,LTD

Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	℃
Storage Temperature	TST	-30	—	+80	℃

Electrical Characteristics

TFT LCD Module

Item	Symbol	Min.	Typ.	Max.	Unit
Supply Voltage	VDD	3.0	3.3	3.6	V
	VGH	17.0	18.0	19.0	V
	VGL	-11	-10	-9	V
	AVDD	11.8	12	12.2	V
VCOM	VCOM	4.5	4.88	5.2	V
Input signal voltage	ViH	0.7 VDD	-	VDD	V
	ViL	0	-	0.3 VDD	V
Output signal voltage	VoH	0.8 VDD	-	-	V
	VoL	0	-	0.2 VDD	V
Current of power supply	IDD	-	25	38	mA
	IADD	-	13.5	25	mA
	IGH	-	3	4.5	mA
	IGL	-	-3	-4.5	mA
	Ivcom	-	23	35	uA

WINSTAR DISPLAY CO., LTD

Interface

LCM PIN Definition
Match connector: Molex 5051104091 or Equivalent


Pin No.	Symbol	I/O	Function
1	GND	P	Ground
2	NC	---	No connection
3	VLED+	P	LED Anode
4	VLED+	P	LED Anode
5	NC	---	No connection
6	VLED-	P	LED Cathode
7	VLED-	P	LED Cathode
8	NC	---	No connection
9	GND	P	Ground
10	NC	---	No connection
11	AVDD	P	Power supply for analog circuit
12	NC	---	No connection
13	VGH	P	Power supply for analog circuit
14	NC	---	No connection
15	VGL	P	Power supply for analog circuit
16	NC	---	No connection
17	GND	P	Ground
18	VCOM	P	Power supply for common voltage
19	GND	P	Ground
20	GND	P	Ground
21	RESET	I	Global reset
22	VDD	P	Power supply for digital circuits
23	STBYB	I	Standby mode, Normally pulled high STBYB = “1”, normal operation STBYB = “0”, timing controller, source driver will turn off, all output are High-Z
24	NC	-	No connection
25	GND	P	Ground
26	D0P	I	MIPI Data Input Lane0 positive-end
27	D0N	I	MIPI Data Input Lane0 negtive-end
28	GND	P	Ground
29	D1P	I	MIPI Data Input Lane1 positive-end

WINSTAR DISPLAY CO.,LTD

30	D1N	I	MIPI Data Input Lane1 negtive-end
31	GND	P	Ground
32	CLKP	I	MIPI Clock Input positive-end
33	CLKN	I	MIPI Clock Input negtive-end
34	GND	P	Ground
35	D2P	I	MIPI Data Input Lane2 positive-end
36	D2N	I	MIPI Data Input Lane2 negtive-end
37	GND	P	Ground
38	D3P	I	MIPI Data Input Lane3 positive-end
39	D3N	I	MIPI Data Input Lane3 negtive-end
40	GND	P	Ground

WINSTAR DISPLAY CO., LTD

Contour Drawing




The non-specified tolerance of dimension is ±0.3 mm .

WINSTAR DISPLAY CO.,LTD

CN1

PIN NO	SYMBOL	PIN NO	SYMBOL
1	GND	21	RESET
2	NC	22	VDD
3	VLED+	23	STBYB
4	VLED+	24	NC
5	NC	25	GND
6	VLED-	26	D0P
7	VLED-	27	D0N
8	NC	28	GND
9	GND	29	D1P
10	NC	30	D1N
11	AVDD	31	GND
12	NC	32	CLKP
13	VGH	33	CLKN
14	NC	34	GND
15	VGL	35	D2P
16	NC	36	D2N
17	GND	37	GND
18	VCOM	38	D3P
19	GND	39	D3N
20	GND	40	GND



The non-specified tolerance of dimension is ±0.3 mm .

WINSTAR DISPLAY CO., LTD