

TFT DISPLAY SPECIFICATION



WINSTAR Display Co.,Ltd.
華凌光電股份有限公司



SPECIFICATION

MODULE NO.: WF0340ATYAB7MNN0

General Specifications

Item	Dimension	Unit
Size	3.4	inch
Dot Matrix	800 x RGB x 800 (TFT)	dots
Module dimension	94.9 (W) x 96.95 (H) x 2.22 (D)	mm
Active area	87.6 x 87.6	mm
Pixel pitch	0.1095 x 0.1095	mm
LCD type	TFT, Normally black, Transmissive	
Viewing Angle	85/85/85/85	
IC	ILI9881C or equivalent	
TFT Interface	4-Lanes MIPI	
Backlight Type	LED, Normally White	
With /Without TP	Without TP	
Surface	Anti-Glare	

*Color tone slight changed by temperature and driving voltage.

Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	°C
Storage Temperature	TST	-30	—	+80	°C
Power Supply voltage 1	VCI~GND	-0.3	—	+3.6	V
Power Supply voltage 2	IOVCC~GND	-0.3	—	+3.3	V
Logic Input Voltage Range	VIN	-0.3	—	IOVCC+0.3	V
Logic Output Voltage Range	VO	-0.3	—	IOVCC+0.3	V

*The absolute maximum rating values of this product are not allowed to be exceeded at any times. Should a module be used with any of the absolute maximum ratings exceeded, the characteristics of the module may not be recovered, or in an extreme case, the module may be permanently destroyed.

Electrical Characteristics

Operating conditions:

Item	Symbol	Min	Typ	Max	Unit
Supply voltage for analog circuit	VCI	2.5	3.3	3.6	V
Supply voltage for logic circuit	IOVCC	1.65	1.8	3.3	V
Current for VCI	I-vci	-	20	30	mA
Current for IOVCC	I-iovcc	-	20	30	mA
Input voltage "H" level	VIH	0.7*IOVCC	—	IOVCC	V
Input voltage "L" level	VIL	GND	—	0.3*IOVCC	V
Output voltage "H" level	VOH	0.8*IOVCC	—	IOVCC	V
Output voltage "L" level	VOL	GND	—	0.2*IOVCC	V


Interface

LCM PIN Definition

Pin	Symbol	Function	Remark
1	VLED+	VLED backlight anode.	
2	VLED-	VLED backlight cathode.	
3	VLED-	VLED backlight cathode.	
4	VCI	Power supply for the analog power	
5	IOVCC	Power supply for the logic power and I/O circuit (IOVCC = VDDI)	
6	RESET	Reset signal(low active) (RESET=RESX)	
7	TE	Tearing effect output	
8	NC	No connection	
9	GND	Power ground	
10	D0P	MIPI-DSI data lane 0 positive input pin.	
11	D0N	MIPI-DSI data lane 0 negative input pin	
12	GND	Power ground	
13	D1P	MIPI-DSI data lane 1 positive input pin.	
14	D1N	MIPI-DSI data lane 1 negative input pin.	
15	GND	Power ground	

16	CLKP	MIPI-DSI data lane positive input pin.	
17	CLKN	MIPI-DSI data lane negative input pin.	
18	GND	Power ground	
19	D2P	MIPI-DSI data lane 2 positive input pin.	
20	D2N	MIPI-DSI data lane 2 negative input pin	
21	GND	Power ground	
22	D3P	MIPI-DSI data lane 3 positive input pin.	
23	D3N	MIPI-DSI data lane 3 negative input pin	
24	GND	Power ground	
25-30	NC	No connection	

Contour Drawing



The non-specified tolerance of dimension is ±0.3 mm .