

# TFT DISPLAY SPECIFICATION



WINSTAR Display Co.,Ltd.  
華凌光電股份有限公司



# Winstar Display Co., LTD

## 華凌光電股份有限公司



WEB: <https://www.winstar.com.tw> E-mail: sales@winstar.com.tw

### SPECIFICATION

**MODULE NO.: WF57A4TLFFDATA**

### General Specifications

Item	Dimension	Unit
Size	5.7	inch
Dot Matrix	640 x RGB x 480(TFT)	dots
Module dimension	125.0 x 98.8 x 11.25(MAX)	mm
Active area	115.2 x 86.4	mm
Pixel pitch	0.18 x 0.18	mm
LCD type	TFT, Normally White, Transmissive	
View Direction	6 o'clock	
Gray Scale Inversion Direction	12 o'clock	
Aspect Ratio	4:3	
Controller IC	SSD1963	
Interface	Digital 8080 family MPU	
Drive IC	HX8250+HX8678	
Backlight Type	LED ,Normally White	
Touch Panel	Resistive Touch Panel, RTP	
Surface	Anti-Glare	

# Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	°C
Storage Temperature	TST	-30	—	+80	°C

# Electrical Characteristics

Operating conditions:

Item	Symbol	Condition	Min	Typ	Max	Unit
Supply Voltage For LCM	VDD	—	3.0	3.3	3.6	V
Supply Current For LCM	IDD	—	—	9	—	mA

LED driving conditions

Parameter	Symbol	Min.	Typ.	Max.	Unit
LED current	-	-	60	-	mA
Power Consumption	--	-	1386	1479	mW
LED voltage	VBL+	18.9	23.1	24.5	V
LED Life Time		-	50,000	-	Hr

# Interface

## LCM PIN Definition

Pin No.	Symbol	Description
1	GND	System ground pin of the IC. Connect to System ground.
2	VDD	Power Supply : +3.3V
3	NC	No connection
4	D/C	Data/Command select
5	WR	Write strobe signal
6	RD	Read strobe signal
7	DB0	Data bus
8	DB1	Data bus
9	DB2	Data bus
10	DB3	Data bus
11	DB4	Data bus
12	DB5	Data bus
13	DB6	Data bus
14	DB7	Data bus
15	CS	Chip select
16	UD	Up/down selection
17	LR	Left /right selection
18	RST	Hardware reset
19	NC	No connection
20	NC	No connection

