

TFT DISPLAY SPECIFICATION



WINSTAR Display Co.,Ltd.
華凌光電股份有限公司



Winstar Display Co., LTD

華凌光電股份有限公司



WEB: <https://www.winstar.com.tw> E-mail: sales@winstar.com.tw

SPECIFICATION

MODULE NO.: WF0154ATAAA4DSN0#

General Specifications

Item	Dimension	Unit
Size	1.54"	inch
Dot Matrix	240 x RGB x 240	dots
Module dimension	31.52 x 33.72 x 1.94	mm
Active area	27.72 x 27.72	mm
Pixel pitch	0.1155 x 0.1155	mm
LCD type	TFT, Normally Black, Transmissive	
Viewing Angle	80/80/80/80	
Backlight Type	LED, Normally White	
Drive IC	ST7789T3-G4-1 or Equivalent	
TFT Interface	SPI	
Touch Panel	Without Touch Panel	
Surface	Anti-Glare	

*Color tone slight changed by temperature and driving voltage.

Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-10	—	+60	°C
Storage Temperature	TST	-20	—	+70	°C

Electrical Characteristics

TFT LCD MODULE

Parameter	Symbol	Value			Unit
		Min.	Typ.	Max.	
Analog Supply Voltage	VDD	2.4	2.8	3.3	V
Power Supply for I/O System	IOVCC	1.65	1.8	3.3	V
Input High Voltage	VIH	0.7 IOVCC	-	IOVCC	V
Input Low Voltage	VIL	GND	-	0.3 IOVCC	mA
Output High Voltage	VoH	0.8 IOVCC	-	IOVCC	mA
Output Low Voltage	VoL	GND	-	0.2 IOVCC	W
(Panel+LSI) Power Consumption	Black Mode	-	6.0	-	mA
	Sleeping Mode	-	0.015	-	mA

Interface

1. LCM PIN Definition

Pin No.	Symbol	Function
1	GND	Ground.
2	IOVCC	Power Supply for I/O System
3	CS	Chip selection pin
4	RESET	This signal will reset the device
5	RS	Display data/command selection pin in 4-line serial interface
6	GND	Ground.
7	SCL	This pin is used to be serial interface clock
8	SDA	SPI interface input/output pin
9	GND	Ground.
10	VDD	Power Supply for Analog
11	FMARK	Tearing effect signal is used to synchronize MCU to frame memory writing.
12	VLED-	Power Supply For LED Backlight Cathode Input
13	VLED-	Power Supply For LED Backlight Cathode Input.
14	VLED+	Power Supply For LED Backlight Anode Input.
15	VLED+	Power Supply For LED Backlight Anode Input.

Contour Drawing

